

# Package: arse (via r-universe)

August 21, 2024

**Version** 1.1.0

**Date** 2019-05-12

**Title** Area of Resilience to Stress Event

**Depends** R (>= 3.5.0), dplyr, pracma

**Description** A method for quantifying resilience after a stress event.

A set of functions calculate the area of resilience that is created by the departure of baseline 'y' (i.e., robustness) and the time taken 'x' to return to baseline (i.e., rapidity) after a stress event using the Cartesian coordinates of the data.

This package has the capability to calculate areas of resilience, growth, and cases in which resilience is not achieved (e.g., diminished performance without return to baseline).

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** TRUE

**URL** <https://github.com/nr3xe/arse>

**RoxygenNote** 6.1.1

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**Repository** <https://nr3xe.r-universe.dev>

**RemoteUrl** <https://github.com/nr3xe/arse>

**RemoteRef** HEAD

**RemoteSha** 36814fd48a334c3a9dd30df5a9ec619bb920679f

## Contents

aog . . . . .	2
arse . . . . .	3
arsefigures . . . . .	4

arise_s . . . . .	5
arise_t . . . . .	6
arise_ts . . . . .	7
count_rapidity . . . . .	8
getintersectx . . . . .	9
mean_robust . . . . .	10
plot_arise . . . . .	11
stress_appraisal . . . . .	12
ynadir . . . . .	13

## Index 14

---

aog	<i>Calculates the area of growth above a baseline.</i>
-----	--

---

### Description

This function takes a series of 'x,y' coordinates and a specified 'y' baseline value. For a given set of x-coordinates over time and repeated measures of a 'y' variable, this function calculates the area of growth (aog) that is formed above the specified baseline value of 'y' using an implementation of the shoelace formula (Gauss's area formula) for the area of irregular polygons. Larger aog values are indicative of more growth on the measured variable.

### Usage

```
aog(data, xcoord, ycoord, ybase = NA, yinvert = FALSE,
     saveout = FALSE)
```

### Arguments

data	A dataframe with x- and y-coordinates in wide format.
xcoord	A specified selection of the x-coordinate values within the dataframe. The first x-coordinate value should correspond to the baseline input of 'y'.
ycoord	A specified selection of the y-coordinate values within the dataframe. The first y-coordinate value should correspond to the baseline value of 'y'. The second y-coordinate value should be the first measure of 'y' after the intrusion of a stress event. The last value of 'y' should correspond to the last measurement of 'y' over the measured timeframe.
ybase	A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.
yinvert	Specifies whether resilience occurs above or below the baseline depending on the meaning of high and low 'y' values. When parameter 'yinvert' is set to 'FALSE' (the default), it is assumed that higher numbers are indicative of positive (i.e., desired) 'y' values (e.g., exam grade). When 'yinvert' is set to 'TRUE', it is assumed that lower numbers are indicative of positive (i.e., desired) 'y' values (e.g., blood pressure).

**saveout** When the parameter 'saveout' is set to 'FALSE' (the default), a vector of calculated aog values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated aog values.

### Value

When the parameter 'saveout' is set to 'FALSE', a vector of calculated aog values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated aog values.

### Examples

```
xc <- t(c(1,2,3,4,5,6,7,8,9,10))
yc <- t(c(75,53,37,25,27,95,80,75,75,75))
dataset1 <- data.frame(xc, yc)
aog(data = dataset1, xcoord = dataset1[,1:10], ycoord = dataset1[,11:20], saveout = TRUE)
```

---

arse *Calculates the area of resilience to stress event below a baseline.*

---

### Description

This function takes a series of 'x,y' coordinates and a specified 'y' baseline value. For a given set of x-coordinates over time and repeated measures of a 'y' variable, this function calculates the area of resilience to a stress event (arse) that is formed below the specified baseline value of 'y' using an implementation of the shoelace formula (Gauss's area formula) for the area of irregular polygons. Any area above the baseline (i.e., growth) is ignored. Smaller arse values are indicative of better resilience on the measured variable.

### Usage

```
arse(data, xcoord, ycoord, ybase = NA, yinvert = FALSE,
      saveout = FALSE)
```

### Arguments

**data** A dataframe with x- and y-coordinates in wide format.

**xcoord** A specified selection of the x-coordinate values within the dataframe. The first x-coordinate value should correspond to the baseline input of 'y'.

**ycoord** A specified selection of the y-coordinate values within the dataframe. The first y-coordinate value should correspond to the baseline value of 'y'. The second y-coordinate value should be the first measure of 'y' after the intrusion of a stress event. The last value of 'y' should correspond to the last measurement of 'y' over the measured timeframe.

**ybase** A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.

yinvert	Specifies whether resilience occurs above or below the baseline depending on the meaning of high and low 'y' values. When parameter 'yinvert' is set to 'FALSE' (the default), it is assumed that higher numbers are indicative of positive (i.e., desired) 'y' values (e.g., exam grade). When 'yinvert' is set to 'TRUE', it is assumed that lower numbers are indicative of positive (i.e., desired) 'y' values (e.g., blood pressure).
saveout	When the parameter 'saveout' is set to 'FALSE' (the default), a vector of calculated arse values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated arse values.

### Value

When the parameter 'saveout' is set to 'FALSE', a vector of calculated arse values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated arse values.

### Examples

```
xc <- t(c(1,2,3,4,5,6,7,8,9,10))
yc <- t(c(75,53,37,25,27,35,50,75,75,75))
dataset1 <- data.frame(xc, yc)
arse(data = dataset1, xcoord = dataset1[,1:10], ycoord = dataset1[,11:20], saveout = TRUE)
```

---

arsetfigures

*arsetfigures*

---

### Description

Dataset used to demonstrate different manifestations of arse. Cases correspond to different figures from a forthcoming arse method paper. Figure number and panel are noted '#' in the last column. Additional data is also added to test other situations that might occur with data sources (e.g., different baselines, interpolation of points).

### Usage

bar

### Format

A dataframe with 11 rows and 22 columns. There are 10 total examples.

---

arise_s	<i>Calculates the area of resilience to stress event below a baseline with scaling for end state growth or non-resilience.</i>
---------	--

---

### Description

This function takes a series of 'x,y' coordinates and a specified 'y' baseline value. For a given set of x-coordinates over time and repeated measures of a 'y' variable, this function calculates the area of resilience to a stress event (arise) that is formed below the specified baseline value of 'y' using an implementation of the shoelace formula (Gauss's area formula) for the area of irregular polygons. With arise calculated, the arise is scaled in reference to the end state value by multiplying the arise value by the division of baseline value over the end state value (i.e., last measured value of 'y') or  $arisevalue * (baselinevalue/endstatevalue)$ . Smaller arise\_s values are indicative of better resilience on the measured variable.

### Usage

```
arise_s(data, xcoord, ycoord, ybase = NA, yend = NA, yinvert = FALSE,
        saveout = FALSE)
```

### Arguments

data	A dataframe with x- and y-coordinates in wide format.
xcoord	A specified selection of the x-coordinate values within the dataframe. The first x-coordinate value should correspond to the baseline input of 'y'.
ycoord	A specified selection of the y-coordinate values within the dataframe. The first y-coordinate value should correspond to the baseline value of 'y'. The second y-coordinate value should be the first measure of 'y' after the intrusion of a stress event. The last value of 'y' should correspond to the last measurement of 'y' over the measured timeframe.
ybase	A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.
yend	A specified selection of the end state of the 'y' measured variable. Users are advised to place end state as the last instance of the y-coordinate values. Function defaults to use the last y-coordinate value in the series.
yinvert	Specifies whether resilience occurs above or below the baseline depending on the meaning of high and low 'y' values. When parameter 'yinvert' is set to 'FALSE' (the default), it is assumed that higher numbers are indicative of positive (i.e., desired) 'y' values (e.g., exam grade). When 'yinvert' is set to 'TRUE', it is assumed that lower numbers are indicative of positive (i.e., desired) 'y' values (e.g., blood pressure).
saveout	When the parameter 'saveout' is set to 'FALSE' (the default), a vector of calculated arise_s values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated arise_s values.

**Value**

When the parameter 'saveout' is set to 'FALSE', a vector of calculated arse\_s values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated arse\_s values.

**Examples**

```
xc <- t(c(1,2,3,4,5,6,7,8,9,10))
yc <- t(c(75,53,37,25,27,35,46,49,49,51))
dataset1 <- data.frame(xc, yc)
arse_s(data = dataset1, xcoord = dataset1[,1:10], ycoord = dataset1[,11:20], saveout = TRUE)
```

---

arset	<i>Calculates the area of resilience to stress event below a baseline with subtraction of area of growth.</i>
-------	---

---

**Description**

This function takes a series of 'x,y' coordinates and a specified 'y' baseline value. For a given set of x-coordinates over time and repeated measures of a 'y' variable, this function calculates the area of resilience to a stress event (arse) that is formed below the specified baseline value of 'y' using an implementation of the shoelace formula (Gauss's area formula) for the area of irregular polygons. Area of growth (aog) is calculated in the same manner by calculating the area formed by points above the baseline. With both areas calculated, the arse is subtracted from aog creating a new variable, arset. Smaller arset values are indicative of better resilience on the measured variable.

**Usage**

```
arset(data, xcoord, ycoord, ybase = NA, yinvert = FALSE,
      saveout = FALSE)
```

**Arguments**

data	A dataframe with x- and y-coordinates in wide format.
xcoord	A specified selection of the x-coordinate values within the dataframe. The first x-coordinate value should correspond to the baseline input of 'y'.
ycoord	A specified selection of the y-coordinate values within the dataframe. The first y-coordinate value should correspond to the baseline value of 'y'. The second y-coordinate value should be the first measure of 'y' after the intrusion of a stress event. The last value of 'y' should correspond to the last measurement of 'y' over the measured timeframe.
ybase	A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.

yinvert	Specifies whether resilience occurs above or below the baseline depending on the meaning of high and low 'y' values. When parameter 'yinvert' is set to 'FALSE' (the default), it is assumed that higher numbers are indicative of positive (i.e., desired) 'y' values (e.g., exam grade). When 'yinvert' is set to 'TRUE', it is assumed that lower numbers are indicative of positive (i.e., desired) 'y' values (e.g., blood pressure).
saveout	When the parameter 'saveout' is set to 'FALSE' (the default), a vector of calculated arise_t values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated arise_t values.

### Value

When the parameter 'saveout' is set to 'FALSE', a vector of calculated arise\_t values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated arise\_t values.

### Examples

```
xc <- t(c(1,2,3,4,5,6,7,8,9,10))
yc <- t(c(75,53,37,25,27,95,80,75,75,75))
dataset1 <- data.frame(xc, yc)
arise_t(data = dataset1, xcoord = dataset1[,1:10], ycoord = dataset1[,11:20], saveout = TRUE)
```

---

arise_ts	<i>Calculates the area of resilience to stress event below a baseline with subtraction of area of growth and scaling for end state growth or non-resilience.</i>
----------	--

---

### Description

This function takes a series of 'x,y' coordinates and a specified 'y' baseline value. For a given set of x-coordinates over time and repeated measures of a 'y' variable, this function calculates the area of resilience to a stress event (arise) that is formed below the specified baseline value of 'y' using an implementation of the shoelace formula (Gauss's area formula) for the area of irregular polygons. The function also calculates the area of growth (aog) that is formed above the specified baseline in the same manner as arise. The function then subtracts the arise from aog to get a new variable, arise\_t. With arise\_t calculated, it is scaled in reference to the end state value by (a) if arise\_t is greater than or equal to zero, multiplying the arise\_t value by the division of baseline value over the end state value (i.e., last measured value of 'y') or  $arise\_t * (baseline\_value / end\_state\_value)$  or (b) if arise\_t is less than zero, multiplying the arise\_t value by the division of end state value over the baseline value (i.e., last measured value of 'y') or  $arise\_t * (end\_state\_value / baseline\_value)$ . Smaller arise\_s values are indicative of better resilience on the measured variable.

### Usage

```
arise_ts(data, xcoord, ycoord, ybase = NA, yend = NA, yinvert = FALSE,
         saveout = FALSE)
```

**Arguments**

data	A dataframe with x- and y-coordinates in wide format.
xcoord	A specified selection of the x-coordinate values within the dataframe. The first x-coordinate value should correspond to the baseline input of 'y'.
ycoord	A specified selection of the y-coordinate values within the dataframe. The first y-coordinate value should correspond to the baseline value of 'y'. The second y-coordinate value should be the first measure of 'y' after the intrusion of a stress event. The last value of 'y' should correspond to the last measurement of 'y' over the measured timeframe.
ybase	A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.
yend	A specified selection of the end state of the 'y' measured variable. Users are advised to place end state as the last instance of the y-coordinate values. Function defaults to use the last y-coordinate value in the series.
yinvert	Specifies whether resilience occurs above or below the baseline depending on the meaning of high and low 'y' values. When parameter 'yinvert' is set to 'FALSE' (the default), it is assumed that higher numbers are indicative of positive (i.e., desired) 'y' values (e.g., exam grade). When 'yinvert' is set to 'TRUE', it is assumed that lower numbers are indicative of positive (i.e., desired) 'y' values (e.g., blood pressure).
saveout	When the parameter 'saveout' is set to 'FALSE' (the default), a vector of calculated arse_ts values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated arse_ts values.

**Value**

When the parameter 'saveout' is set to 'FALSE', a vector of calculated arse\_ts values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated arse\_ts values.

**Examples**

```
xc <- t(c(1,2,3,4,5,6,7,8,9,10))
yc <- t(c(75,75,77,79,80,81,77,76,77,77))
dataset1 <- data.frame(xc, yc)
arse_ts(data = dataset1, xcoord = dataset1[,1:10], ycoord = dataset1[,11:20], saveout = TRUE)
```

---

count\_rapidity

*Calculates a count of the time beneath the baseline.*


---

**Description**

This function takes a series of y-coordinates and returns a count of y-coordinates that fall beneath the specified baseline after the intrusion of a stress event (i.e., rapidity).



**Usage**

```
count_rapidity(data, ycoord, ybase = NA, yinvert = FALSE,
               saveout = FALSE)
```

**Arguments**

data	A dataframe with x- and y-coordinates in wide format.
ycoord	A specified selection of the y-coordinate values within the dataframe. The first y-coordinate value should correspond to the baseline value of 'y'. The second y-coordinate value should be the first measure of 'y' after the intrusion of a stress event. The last value of 'y' should correspond to the last measurement of 'y' over the measured timeframe.
ybase	A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.
yinvert	Specifies whether resilience occurs above or below the baseline depending on the meaning of high and low 'y' values. When parameter 'yinvert' is set to 'FALSE' (the default), it is assumed that higher numbers are indicative of positive (i.e., desired) 'y' values (e.g., exam grade). When 'yinvert' is set to 'TRUE', it is assumed that lower numbers are indicative of positive (i.e., desired) 'y' values (e.g., blood pressure).
saveout	When the parameter 'saveout' is set to 'FALSE' (the default), a vector of calculated count_rapidity values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated count_rapidity values.

**Value**

When the parameter 'saveout' is set to 'FALSE', a vector of calculated count\_rapidity values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated count\_rapidity values.

**Examples**

```
xc <- t(c(1,2,3,4,5,6,7,8,9,10))
yc <- t(c(75,53,37,25,27,35,50,75,75,75))
dataset1 <- data.frame(xc, yc)
count_rapidity(data = dataset1, ycoord = dataset1[,11:20], saveout = TRUE)
```

**Description**

This function takes a series of 'x,y' coordinates and a specified 'y' baseline value. For any two sequential x-coordinate points, where the 'y' baseline value is crossed in between them, the function calculates the predicted x-coordinate value and interpolates that point with the matching 'y' baseline value. The new points are then added to the original set of 'x,y' coordinates. Note that all the prefixed arse functions automatically perform this operation within their respective functions.

**Usage**

```
getintersectx(data, xcoord, ycoord, ybase = NA)
```

**Arguments**

data	A dataframe with x- and y-coordinates in wide format.
xcoord	A specified selection of the x-coordinate values within the dataframe.
ycoord	A specified selection of the y-coordinate values within the dataframe.
ybase	A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.

**Value**

A dataframe of old and newly-interpolated x-coordinate values at the specified baseline.

**Examples**

```
xc <- t(c(1,2,3,4,5,6,7,8,9,10))
yc <- t(c(75,53,37,25,95,35,50,75,75,75))
dataset1 <- data.frame(xc, yc)
getintersectx(data = dataset1, xcoord = dataset1[,1:10], ycoord = dataset1[,11:20])
```

---

mean\_robust

*Calculates the mean robustness after a stress event.*

---

**Description**

This function takes a series of y-coordinates and returns the average deviation from the specified baseline after the intrusion of a stress event (i.e., robustness). Magnitude is indicated by how large the mean\_robust value becomes. Direction of the robustness is indicated by a positive or negative value; negative numbers indicate a departure below the baseline while positive numbers indicate a departure above the baseline.

**Usage**

```
mean_robust(data, ycoord, ybase = NA, yinvert = FALSE,
            saveout = FALSE)
```

**Arguments**

data	A dataframe with x- and y-coordinates in wide format.
ycoord	A specified selection of the y-coordinate values within the dataframe. The first y-coordinate value should correspond to the baseline value of 'y'. The second y-coordinate value should be the first measure of 'y' after the intrusion of a stress event. The last value of 'y' should correspond to the last measurement of 'y' over the measured timeframe.
ybase	A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.
yinvert	Specifies whether resilience occurs above or below the baseline depending on the meaning of high and low 'y' values. When parameter 'yinvert' is set to 'FALSE' (the default), it is assumed that higher numbers are indicative of positive (i.e., desired) 'y' values (e.g., exam grade). When 'yinvert' is set to 'TRUE', it is assumed that lower numbers are indicative of positive (i.e., desired) 'y' values (e.g., blood pressure).
saveout	When the parameter 'saveout' is set to 'FALSE' (the default), a vector of calculated mean_robust values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated mean_robust values.

**Value**

When the parameter 'saveout' is set to 'FALSE', a vector of calculated mean\_robust values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated mean\_robust values.

**Examples**

```
yc <- t(c(75,53,37,25,27,35,50,75,75,75))
dataset1 <- data.frame(yc)
mean_robust(data = dataset1, ycoord = yc, saveout = TRUE)
```

---

plot\_arise

*Plots the area of resilience to stress event.*


---

**Description**

This function takes a series of 'x,y' coordinates and a specified 'y' baseline value and plots them on an x- and y-axis.

**Usage**

```
plot_arise(xcoord, ycoord, ybase = NA, ll, ul, xlab = NA, ylab = NA)
```

**Arguments**

xcoord	A specified selection of the x-coordinate values within a vector. The first x-coordinate value should correspond to the baseline input of 'y'.
ycoord	A specified selection of the y-coordinate values within a vector. The first y-coordinate value should correspond to the baseline value of 'y'. The second y-coordinate value should be the first measure of 'y' after the intrusion of a stress event. The last value of 'y' should correspond to the last measurement of 'y' over the measured timeframe.
ybase	A specified selection of the baseline of the 'y' measured variable. Users are advised to place baseline as the first instance of the y-coordinate values. Function defaults to use the first y-coordinate value in the series.
ll	Sets the lower limit of the y-axis scale. Recommended to be the lowest possible value of your 'y' measure.
ul	Sets the upper limit of the y-axis scale. Recommended to be the highest possible value of your 'y' measure.
xlab	Labels the x-axis. Defaults to "Time (X)".
ylab	Labels the y-axis. Defaults to "Outcome (Y)".

**Value**

Returns a graph with 'x,y' coordinates and baseline.

**Examples**

```
xc <- t(c(1,2,3,4,5,6,7,8,9,10))
yc <- t(c(75,53,37,25,27,35,50,75,75,75))
dataset1 <- data.frame(xc, yc)
plot_arise(xcoord = as.numeric(dataset1[,1:10]),
           ycoord = as.numeric(dataset1[,11:20]), ll = 0, ul = 100)
```

---

stress\_appraisal      *stress\_appraisal*

---

**Description**

Fictitious dataset used to demonstrate the calculation of arse. In this dataset, there are 50 fictitious cases split into two groups with 25 members each (i.e., 'group' variable). The control condition represents cases in which training was not given before a stress event. In the 'Appraisal\_Training' condition, cases were given a training to help cognitively reappraise a stressful situation and think of strategies to adapt to a stressor. Before random assignment to group condition, a baseline (i.e., 'tby') is measured on the case's ability to place 100 colored-pegs in a specified patterned grid in one minute. Following baseline measurement, a stress event occurs for all cases where they are asked to dip their hand in a bath of ice cold water for one minute (or as long as they can stand). Following the stress event, the cases are asked to perform the peg task four more times with different patterns to match. Cases perform the peg task at three minute intervals. The fourth time the case performs the task (i.e., t4y) represents the case's endstate at the end of the fictitious experiment. In the dataset, t#x values represent time on the x-axis.

**Usage**

```
bar
```

**Format**

A dataframe with 51 rows and 12 columns. There are 50 total cases.

**Source**

Fictitious dataset. All values generated.

---

ynadir	<i>Calculates the nadir point of measured 'y' values.</i>
--------	---

---

**Description**

This function takes a series of y-coordinates and returns the lowest value.

**Usage**

```
ynadir(data, ycoord, yinvert = FALSE, saveout = FALSE)
```

**Arguments**

data	A dataframe with x- and y-coordinates in wide format.
ycoord	A specified selection of the y-coordinate values within the dataframe.
yinvert	Specifies whether resilience occurs above or below the baseline depending on the meaning of high and low 'y' values. When parameter 'yinvert' is set to 'FALSE' (the default), it is assumed that higher numbers are indicative of positive (i.e., desired) 'y' values (e.g., exam grade). When 'yinvert' is set to 'TRUE', it is assumed that lower numbers are indicative of positive (i.e., desired) 'y' values (e.g., blood pressure).
saveout	When the parameter 'saveout' is set to 'FALSE' (the default), a vector of calculated ynadir values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated ynadir values.

**Value**

When the parameter 'saveout' is set to 'FALSE', a vector of calculated ynadir values are given for each case. When 'saveout' is set to 'TRUE', a dataframe of the original inputted dataset is returned with a new column of calculated ynadir values.

**Examples**

```
yc <- t(c(75,53,37,25,27,35,50,75,75,75))
dataset1 <- data.frame(yc)
ynadir(data = dataset1, ycoord = yc, saveout = TRUE)
```

# Index

## \* datasets

- arsetfigures, 4
- stress\_appraisal, 12

aog, 2

arse, 3

arse\_s, 5

arse\_t, 6

arse\_ts, 7

arsetfigures, 4

count\_rapidity, 8

getintersectx, 9

mean\_robust, 10

plot\_arse, 11

stress\_appraisal, 12

ynadir, 13